

# FLOS

03.4213.B1 White

## Easy Kap 80 Square Adjustable


Designed by FLOS Architectural, 2016



Recessed luminaire with main voltage source. Installation frame not necessary.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED retrofit
Lamp type	PAR16
Lamp holders	GZ10
Number of lamps	1

### Physical

Colour	White
Trim	Yes
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Recessed depth (mm)	155
Spot diameter (mm)	80
Length (mm)	80
Net weight (kg)	0.12
Package height (mm)	90
Package width (mm)	140
Package length (mm)	105
IP internal	20
IP external	23

### Download

[Mounting instructions](#)  PDF

[Item information](#)  JPG

### Ecodesign and Energy Labelling

  Replaceable (LED only) light source by an end-user



## Photometric

Lighting type	Direct
Light distribution	Symmetric

## Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240

## Notes

Not suitable for lens accessories.

---