

FLOS

03.4176.74.UQ Black

Easy Kap 80 Square Fixed Optic Spot - Non IC


Designed by FLOS Architectural, 2017



Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	9.2
Source flux (lm)	956
System flux (lm)	696
Efficacy (lm/W)	75

Physical

Color	Black
Trim	Yes
Orientation	Fixed
Spot diameter (in)	3.15
Net weight (lb)	7.77
IP internal	54

Download

Family spec sheet [↓ ZIP](#)


Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C=
Beam angle C0-180 (°)	17
Beam angle C90-270 (°)	17


Electrical

Insulation class	III
Forward voltage (V)	18.2
LED current (mA)	500

Notes

Diffusing lens included


Accessories & Power Supply



REQUIRED Power supply

SP14W500MA-ELV-E01


Splice Box 9"x2"x1.5", 500mA ,
14W, ELV Dimmable, Thermal
120V



REQUIRED Power supply

SP20W500MA-120-V01

Splice Box 9"x2"x1.5", 500mA ,
20W, 0-10V , Dimmable, Thermal
120V




REQUIRED Power supply

Electrical

SP20W500MA-277-V01

Splice Box 9" x 2" x 1.5", 500mA,
20W, 0-10V, 277V



OPTIONAL Housing and Hanger Bar

TRAY-0002

Registration Tray - non electrical,
place holder for non IC new
construction, Square, 2.95 x
2.95"