

# FLOS

03.4176.GLUQ Gold

## Easy Kap 80 Square Fixed Optic Spot - Non IC


Designed by FLOS Architectural, 2017



Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	9.2
Source flux (lm)	956
System flux (lm)	762
Efficacy (lm/W)	82

### Physical

Color	Gold
Trim	Yes
Orientation	Fixed
Spot diameter (in)	3.15
Net weight (lb)	7.77
IP internal	54

### Download

[Family spec sheet](#)  ZIP


[Mounting instructions](#)  PDF

### Photometric Files

[LDT / IES](#)  ZIP



## Schematic light drawing



### Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C=
Beam angle C0-180 (°)	18
Beam angle C90-270 (°)	18


### Electrical

Insulation class	III
Forward voltage (V)	18.2
LED current (mA)	500

### Notes

Diffusing lens included


## Accessories & Power Supply



### REQUIRED Power supply

SP14W500MA-ELV-E01


Splice Box 9"x2"x1.5", 500mA ,  
14W, ELV Dimmable, Thermal  
120V



### REQUIRED Power supply

SP20W500MA-120-V01

Splice Box 9"x2"x1.5", 500mA ,  
20W, 0-10V , Dimmable, Thermal  
120V




### REQUIRED Power supply

#### Electrical

SP20W500MA-277-V01

Splice Box 9" x 2" x 1.5", 500mA,  
20W, 0-10V, 277V



### OPTIONAL Housing and Hanger Bar

TRAY-0002

Registration Tray - non electrical,  
place holder for non IC new  
construction, Square, 2.95 x  
2.95"