


FLOS

03.4219.GL Gold

Easy Kap 80 Square Wall-Washer


Designed by FLOS Architectural, 2016



Recessed luminaire with main voltage source. Installation frame not necessary.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED retrofit
Lamp type	PAR16
Lamp holders	GU10
Number of lamps	1

Physical

Colour	Gold
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	140
Spot diameter (mm)	80
Length (mm)	80
Net weight (kg)	0.12
Package height (mm)	90
Package width (mm)	140
Package length (mm)	105
IP internal	20
IP external	23

Download

[Mounting instructions](#) [↓ PDF](#)
[Item information](#) [↓ JPG](#)

Ecodesign and Energy Labelling

 Replaceable (LED only) light source by an end-user



Photometric

Lighting type	Indirect, Direct
Light distribution	Asymmetric

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240

Notes

Not suitable for lens accessories.
