

Easy Kap Ø 80 Wall-Washer


Designed by FLOS Architectural, 2016



Recessed luminaire with main voltage source. Installation frame not necessary.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED retrofit
Lamp type	PAR16
Lamp holders	GU10
Ilcos	No
Number of heads	1
System power (W)	50
System flux (lm)	464

Physical

Colour	Gold
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	140
Spot diameter (mm)	80
Net weight (kg)	0.12
IP internal	20
IP external	23

Download

Mounting instructions [↓ PDF](#)

Photometric Files


LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)



Ecodesign and Energy Labelling



Replaceable (LED only)
light source by an end-user

Photometric

Lighting type	Indirect, Direct
Light distribution	Asymmetric
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50
Beam angle C0-180 (°)	18
Beam angle C90-270 (°)	20
UGR _L	13

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	230
LED current (mA)	-9
Emergency type	No

Notes

Not suitable for lens accessories.