

03.4196.B1.UQ White

Easy Kap Ø 80 Wall-Washer - Non IC


Designed by FLOS Architectural, 2016



Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	9.2
Source flux (lm)	956
System flux (lm)	622
Efficacy (lm/W)	71

Physical

Color	White
Trim	Yes
Orientation	Fixed
Net weight (lb)	7.77
IP internal	54

Download


Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files

LDT / IES	ZIP
-----------	---------------------



Schematic light drawing



Photometric

Lighting type	Indirect, Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C=
Beam angle C0-180 (°)	28
Beam angle C90-270 (°)	37


Electrical

Insulation class	III
Forward voltage (V)	18.2
LED current (mA)	500

Notes


Elliptical lens included.

Accessories & Power Supply




REQUIRED
Power supply

SP14W500MA-ELV-E01
Splice Box 9"x2"x1.5", 500mA ,
14W, ELV Dimmable, Thermal
120V




REQUIRED
Power supply

SP20W500MA-120-V01
Splice Box9"x2"x1.5", 500mA ,
20W, 0-10V , Dimmable, Thermal
120V



REQUIRED
Power supply

Electrical
SP20W500MA-277-V01
Splice Box 9" x 2" x 1.5", 500mA,
20W, 0-10V, 277V



OPTIONAL
Housing and Hanger Bar

TRAY-0001
Registration Tray - non electrical,
place holder for non IC new
construction, Ø2.95"