

## Easy Kap Ø 80 Wall-Washer - Non IC


Designed by FLOS Architectural, 2016



Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | LED array           |
| Number of lamps        | 1                   |
| Power (W)              | 9.2                 |
| Source flux (lm)       | 956                 |
| System flux (lm)       | 590                 |
| Efficacy (lm/W)        | 67                  |

### Physical

|                 |       |
|-----------------|-------|
| Color           | Gold  |
| Trim            | Yes   |
| Orientation     | Fixed |
| Net weight (lb) | 7.77  |
| IP internal     | 54    |

### Download


|                       |                     |
|-----------------------|---------------------|
| Family spec sheet     | <a href="#">ZIP</a> |
| Mounting instructions | <a href="#">PDF</a> |

### Photometric Files

|           |                     |
|-----------|---------------------|
| LDT / IES | <a href="#">ZIP</a> |
|-----------|---------------------|



Schematic light drawing



Photometric

|                          |                             |
|--------------------------|-----------------------------|
| Lighting type            | Indirect, Direct            |
| Light distribution       | Asymmetric                  |
| CCT (K)                  | 3000                        |
| CRI>                     | 90                          |
| McAdam steps (SDCM)      | 3                           |
| LED Life / Failure Ratio | L80B50>50.000h<br>(Tc=85°C= |
| Beam angle C0-180 (°)    | 30                          |
| Beam angle C90-270 (°)   | 36                          |


Electrical

|                     |      |
|---------------------|------|
| Insulation class    | III  |
| Forward voltage (V) | 18.2 |
| LED current (mA)    | 500  |

Notes


Elliptical lens included.

Accessories & Power Supply




REQUIRED  
Power supply

SP14W500MA-ELV-E01  
Splice Box 9"x2"x1.5", 500mA ,  
14W, ELV Dimmable, Thermal  
120V




REQUIRED  
Power supply

SP20W500MA-120-V01  
Splice Box9"x2"x1.5", 500mA ,  
20W, 0-10V , Dimmable, Thermal  
120V



REQUIRED  
Power supply

Electrical  
SP20W500MA-277-V01  
Splice Box 9" x 2" x 1.5", 500mA,  
20W, 0-10V, 277V



OPTIONAL  
Housing and Hanger Bar

TRAY-0001  
Registration Tray - non electrical,  
place holder for non IC new  
construction, Ø2.95"