

05.8011.40.9S White

## Eclectic 70 Fixed Cone - Non IC Remote Driver


Designed by FLOS Architectural, 2022



Eclectic Ø70. Non-adjustable Downlight. "Cone" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 47° cut-off angle. IP54 water tightness. Alternative options for lenses, orientation modules and style façades are available as spare parts.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	7.5
System flux (lm)	576

### Physical

Color	White
Orientation	Fixed
Recessed depth (in)	4.53
Net weight (lb)	0.36
Package volume (in)	61.02
IP internal	54

### Download

Family spec sheet	ZIP
Mounting instructions	PDF

### Photometric Files


LDT / IES	ZIP
-----------	-----

### Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	2
Rf fidelity index	92
Rg gamut index	98
LED Life / Failure Ratio	L70B50>55.000h_Tc=85°C
Beam angle C0-180 (°)	23
Beam angle C90-270 (°)	23

Electrical

Insulation class	III
Forward voltage (V)	12.3
LED current (mA)	600
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable 1-10V

Ecodesign and Energy Labelling


This product contains a light source of energy efficiency class **G**



Notes

Optional filters to be ordered separately.  
Listings: UL Listed, IP54. Class II  
Installation frame ordered separately. When ordering registration tray the installation frame is included.  
Non IC (requires 3" clearance from insulation) with remote driver. Driver must be located in temperate accessible location.

Accessories & Power Supply



REQUIRED  
Power supply

SP25W600MA-10V-A02  
Splice Box 7"x3-5/8"x1-1/4",  
600mA , 25W, 0-10V Dimmable,  
120/277V



REQUIRED  
Frame

Installation

08.0670.14

Trim Frame



REQUIRED  
Frame

Installation

08.0670.40

Trim Frame




REQUIRED  
Frame

Installation

08.0672.00

No Trim Frame



OPTIONAL  
Accessory

Optical

08.0727.00

Honeycomb for Eclectic 70



OPTIONAL  
Filter

Optical

08.0731.00

Colour Temperature Increaser for  
Eclectic 70



OPTIONAL  
Filter

Optical

08.0732.00

Colour Temperature Decreaser  
for Eclectic 70