



## **Eclectic 70 Fixed Flat - Non IC**

Designed by FLOS Architectural, 2022




LED - LED array - 7.5W - 404lm - 2700K - CRI> 90 - Beam° 15

Eclectic Ø70. Non-adjustable Downlight. "Flat" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 55° cut-off angle. IP54 water tightness. Alternative options for lenses, orientation modules and style façades are available as spare parts.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



## Main specifications

Mounting Ceiling recessed	
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	7.5
System flux (lm)	404

## Physical

Color	White
Orientation	Fixed
Recessed depth (in)	5.27
Net weight (lb)	0.36
Package volume (in)	61.02
IP internal	54

# Download

amily spec sheet	<b>⊥</b> ZIP
Nounting instructions	<b>业</b> PDF

## Photometric Files

LDT / IES



# **Technical Drawings**

2D	<u>↓</u> ZIP
3D	<b>⊥</b> ZIP














https://professional.flos.com/en-US/us/product/eclectic-70-fixed-flat-non-ic-05.8006.40.ug/

05.8006.40.UQ

# Schematic light drawing



Bea	Beam Angle:	
h(m)	) E(lx)	D(m)
1_	5909	0.26
2	1477	0.52
3	657	0.77
4	369	1.03
5	236	1.29

5909 cd 30°	5	2
us flux <b>l</b> uminaire		

## Electrical

Insulation class	II
Forward voltage (V)	12.3
LED current (mA)	600
Driver	Attached Splice Box

# **Ecodesign and Energy** Labelling

This product contains a light source of energy efficiency class **G** 



Replaceable (LED only) light source by an enduser



Replaceable control gear by a professional

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
Rf fidelity index	88
Rg gamut index	94
LED Life / Failure Ratio	L70B50>55.000h_Tc=85°
Beam angle C0-180 (°)	15
Beam angle C90-270 (°)	15

## **Accessories & Power Supply**



REQUIRED

Splice Box 600mA 1-10V for Eclectic 70&90



#### **REQUIRED** Frame

Installation

08.0670.14

Trim Frame



## **REQUIRED** Frame

Installation

Trim Frame



## REQUIRED Frame

Installation

No Trim Frame







## **OPTIONAL** Accessory

Optical

Honeycomb for Eclectic 70

**OPTIONAL** 

Filter

Optical

Colour Temperature Increaser for

Eclectic 70

**OPTIONAL** 

Filter

Optical

Colour Temperature Decreaser for Eclectic 70



6 6 70	00 0744 00
Spot Lens for Eclectic 70	08.0711.00
Medium Lens for Eclectic 70	08.0712.00
Flood Lens for Eclectic 70	08.0713.00
Cone Frontal for Eclectic 70	08.0721.14
Cone Frontal for Eclectic 70	08.0721.40
Soft Frontal for Eclectic 70	08.0722.14
Soft Frontal for Eclectic 70	08.0722.40
Flat Frontal for Eclectic 70	08.0723.14
Flat Frontal for Eclectic 70	08.0723.40
Module Fix for Eclectic 70	08.0739.00
Module Adjustable for Eclectic	08.0740.00
70	









08.0711.00

Spot Lens for Eclectic 70

08.0712.00

Medium Lens for Eclectic 70

08.0713.00

Flood Lens for Eclectic 70

08.0721.14

Cone Frontal for Eclectic 70









08 0721 40

Cone Frontal for Eclectic 70

08.0722.14

Soft Frontal for Eclectic 70

08.0722.40

Soft Frontal for Eclectic 70

08.0723.14

Flat Frontal for Eclectic 70







08.0723.40

Flat Frontal for Eclectic 70

08.0739.00

Module Fix for Eclectic 70

08 0740 00

Module Adjustable for Eclectic 70