



Eclectic 90 Fixed Cone Led Array - Non IC

Designed by FLOS Architectural, 2022




9.6W - 849Im - 2700K - CRI> 90 - Beam° 33

Eclectic Ø90. Non-adjustable Downlight. "Cone" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 41° cut-off angle. IP54 water tightness. Alternative options for lenses, orientation modules and style façades are available as spare parts.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling recessed	
Environments	Indoor dry location	
Light Source Type	LED	
Light sources included	Yes	
LED type	LED array	
Number of lamps	1	
Power (W)	9.6	
System flux (lm)	849	

Physical

Color	White
Recessed depth (in)	4.49
Net weight (lb)	0.64
Package volume (in)	244.09
IP internal	54

Download

Download	
Family spec sheet	⊥ ZIP
Mounting instructions	⊥ PDF

Photometric Files

LDT / IES



Technical Drawings

2D	<u>↓</u> ZIP
3D	⊥ ZIP











Ecodesign and Energy Labelling





Replaceable (LED only) light source by an enduser

https://professional.flos.com/en-US/us/product/eclectic-90-fixed-cone-led-array-non-ic-05.8102.40.ug/

05.8102.40.UQ

Schematic light drawing



Beam Angle:		33°
h(m)	E(lx)	D(m)
1	3029	0.59
2	757	1.18
3	337	1.78
4	189	2.37
5	121	2.96

Luminous flux luminaire 849 lm

Photometric

Lighting type	Direct
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2700
Rf fidelity index	88
Rg gamut index	94
Beam angle C0-180 (°)	33
Beam angle C90-270 (°)	33

Electrical

Insulation class	II
LED current (mA)	275
Driver	Attached Splice Box

Accessories & Power Supply



REQUIRED

Splice Box 275mA 1-10V for Eclectic 90



REQUIRED

Splice Box 275mA for Eclectic 90



REQUIRED Frame

Installation

Trim Frame



REQUIRED Frame

Installation

Trim Frame







REQUIRED Frame

Installation

No Trim Frame



OPTIONAL Accessory

Optical

Honeycomb for Eclectic 90

OPTIONAL

Optical

Filter


Colour Temperature Increaser Filter for Eclectic 90

OPTIONAL

Filter

Optical

Colour Temperature Decreaser for Eclectic 90



Spot Lens for Eclectic 90 Led	08.0714.00
Array	
Medium Lens for Eclectic 90 Led	08.0715.00
Array	
Flood Lens for Eclectic 90 Led	08.0716.00
Array	
Wide Flood Lens for Eclectic 90	08.0717.00
Led Array	
Cone Frontal for Eclectic 90	08.0724.14
Cone Frontal for Eclectic 90	08.0724.40
Soft Frontal for Eclectic 90	08.0725.14
Soft Frontal for Eclectic 90	08.0725.40
Flat Frontal for Eclectic 90	08.0726.14
Flat Frontal for Eclectic 90	08.0726.40
Module Fix for Eclectic 90	08.0741.00
Module Adjustable for Eclectic	08.0742.00
90	









08.0714.00

Spot Lens for Eclectic 90 Led Array

08.0715.00

Medium Lens for Eclectic 90 Led Array

08 0716 00

Flood Lens for Eclectic 90 Led Array

08.0717.00

Wide Flood Lens for Eclectic 90 Led Array









08.0724.14

Cone Frontal for Eclectic 90

08.0724.40

Cone Frontal for Eclectic 90

08.0725.14

Soft Frontal for Eclectic 90

08.0725.40

Soft Frontal for Eclectic 90









08.0726.14

Flat Frontal for Eclectic 90

08 0726 40

Flat Frontal for Eclectic 90

08.0741.00

Module Fix for Eclectic 90

08.0742.00

Module Adjustable for Eclectic 90