

Eclectic 90 Fixed Flat Led Array

Designed by FLOS Architectural, 2022




10.5W - 809lm - 2700K - CRI> 90 - Beam° 24

Eclectic Ø90. Non-adjustable Downlight. "Flat" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 49° cut-off angle. IP54 water tightness. Alternative options for lenses, orientation modules and style façades are available as spare parts.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	10.5
System power (W)	12.6
Lumen Output (lm)	809
Efficacy (lm/W)	77

Physical

Colour	Black
Orientation	Fixed
Recessed depth (mm)	114
Spot diameter (mm)	95
Length (mm)	95
Net weight (kg)	0.29
Package height (mm)	157
Package width (mm)	210
Package length (mm)	135
IP internal	54

Download

Mounting instructions [Download PDF](#)

Photometric Files

LDT / IES [Download ZIP](#)

Technical Drawings


2D [Download ZIP](#)

3D [Download ZIP](#)

[Bim](#) [Download ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
Rf fidelity index	88
Rg gamut index	94
LED Life / Failure Ratio	L70B50>55.000h_Tc=85°C
Beam angle C0-180 (°)	24
Beam angle C90-270 (°)	24
UGR _L	<10

Electrical

Insulation class	III
LED current (mA)	300
Power supply	Remote
Dimmable	Yes
Power supply type	Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Dimmable Push, Dimmable 1-10V, Mains Cut Dimming

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Accessories & Power Supply



REQUIRED
Power supply
Electrical

60.9162
Continuous current power supply
220/240V - 50/60Hz. Adjustable
Current 300mA-13W / 350mA-
15W / 400mA-18W / 450mA-
20W / 500mA-22W / 550mA-
24W / 600mA-27W / 650mA-
29W / 700mA-31W / 750mA-
32W / 800mA-33W / 850mA-
35W / 900mA-38W / 950mA-
40W / 1000/1050mA-4...



REQUIRED
Power supply
Electrical

60.9160
Non dimmable continuous
current power supply of
220/240V - 50/60Hz with power
current selected through
adjustable with switch 200 mA -
8,5W / 250mA - 11W / 300 mA -
13W / 350 mA - 15W / 400 mA -
17,5W / 450 mA - 19,5W / 500
mA - 22W



REQUIRED
Power supply
Electrical

60.9467
20W Constant current power
supply, AC phase-cut adjustable,
trailing & leading edge dimming
(mains dimming), 220/240V -
50/60Hz, with dip-switch
programmable power supply
current. Output current: 900mA -
20W / 850mA - 20W / 800mA -
20W / 750mA - 20W / ...



REQUIRED
Power supply
Electrical

60.9208
Continuous current power supply
of 13-20W - Dim 1-10V&Push -
110/240V - 50/60Hz with power
current selected through
adjustable



REQUIRED
Power supply
Electrical

60.9843



REQUIRED
Power supply
Electrical

60.9713.0300
300mA, 20 W, 220/240 V - 50/60
Hz constant current power
supply. Dimmable by Dali2



REQUIRED
Power supply
Electrical

60.7678



REQUIRED
Frame
Installation

08.0671.14
Trim Frame

Continuous current power supply
20W, 220/240V - 50/60Hz with
power current selected through
adjustable switch. Dimmable 0-
10V/PWM/RX. Output current:
500mA - 21W / 450mA - 19W /
400mA - 17W / 350mA - 15W /
300mA - 12W / 250mA - 10W.

Continuous current supply
source of 240V - 50/60Hz with
dimmable Dali 2, Push dimming.
150mA - 7.8W / 200mA - 10.4W /
250mA - 13W / 300mA - 15.6W /
350mA - 18.2W / 400mA - 20.8W
/ 500mA - 26W / 600mA - 31.2W
/ 700mA - 36.4W / 750mA - 39W
/ 800mA - 41.6...




REQUIRED
Frame

Installation

08.0671.40

Trim Frame



REQUIRED
Frame

Installation

08.0673.00

No Trim Frame




REQUIRED
Power supply

Electrical

60.7785

Constant current power supply
42W, 220-240V CASAMBI
dimmable.



OPTIONAL
Accessory

Optical

08.0728.00

Honeycomb for Eclectic 90



OPTIONAL
Filter

Optical

08.0735.00

Colour Temperature Increaser
Filter for Eclectic 90




OPTIONAL
Filter

Optical

08.0736.00

Colour Temperature Decreaser
for Eclectic 90

Spare Parts



.	Spot Lens for Eclectic 90 Led Array	08.0714.00
.	Medium Lens for Eclectic 90 Led Array	08.0715.00
.	Flood Lens for Eclectic 90 Led Array	08.0716.00
.	Wide Flood Lens for Eclectic 90 Led Array	08.0717.00
.	Cone Frontal for Eclectic 90	08.0724.14
.	Cone Frontal for Eclectic 90	08.0724.40
.	Soft Frontal for Eclectic 90	08.0725.14
.	Soft Frontal for Eclectic 90	08.0725.40
.	Flat Frontal for Eclectic 90	08.0726.14
.	Flat Frontal for Eclectic 90	08.0726.40
.	Module Fix for Eclectic 90	08.0741.00
.	Module Adjustable for Eclectic 90	08.0742.00



08.0714.00
Spot Lens for Eclectic 90 Led
Array



08.0715.00
Medium Lens for Eclectic 90 Led
Array



08.0716.00
Flood Lens for Eclectic 90 Led
Array



08.0717.00
Wide Flood Lens for Eclectic 90
Led Array



08.0724.14
Cone Frontal for Eclectic 90



08.0724.40
Cone Frontal for Eclectic 90



08.0725.14
Soft Frontal for Eclectic 90



08.0725.40
Soft Frontal for Eclectic 90



08.0726.14

Flat Frontal for Eclectic 90



08.0726.40

Flat Frontal for Eclectic 90



08.0741.00

Module Fix for Eclectic 90



08.0742.00

Module Adjustable for Eclectic 90