

Electrical Feed Rod Rose Ø 140 mm

Designed by Vincent Van Duysen, 2017



Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light sources included	no
Number of lamps	1

Physical

Color	White
Trim	No
Length (in)	3.94
IP internal	20



Download

Family spec sheet	ZIP
Mounting instructions	PDF

Electrical

Emergency type No

Notes

The closure terminals will also be electrified and must be ordered separately. Rod with a Ø140 connection rose: a supply rod for remote installation of the power supply through the connection rose. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED
Power supply
LEDSB60W48V-NDM-D01
LED Driver, 48VDC, 60W, Non-Dimming, 120-277V



REQUIRED
Power supply
Electrical
LEDSB30W48V-NDM-D01
LED power supply source for remote installation, 48V/30W



REQUIRED
Power supply
LEDSB96W48V-NDM-D01
LED Driver, 48VDC, 96W, Non-Dimming, 120-277V



REQUIRED
Component
06.5135.14A
End Cap Dali/1-10V/FLOS Control® by Casambi compatible



REQUIRED
Component
06.5135.40A
End Cap Dali/1-10V/FLOS Control® by Casambi compatible



REQUIRED
Component
06.5142.14A
End Cap On board dimmer/FLOS Control® by Casambi compatible



REQUIRED
Component
06.5142.40A
End Cap On board dimmer/FLOS Control® by Casambi compatible