

FLOS

06.5126.14 Black

Electrical Feed Rod Rose Ø 140 mm

Designed by Vincent Van Duysen, 2017



Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Icos	No
Number of heads	1

Physical

Colour	Black
Trim	No
Length (mm)	300
Net weight (kg)	0.84
IP internal	20



Download

Mounting instructions

↓ PDF



Electrical

Emergency type No

Notes

The closure terminals will also be electrified and must be ordered separately. Rod with a Ø140 connection rose: a supply rod for remote installation of the power supply through the connection rose. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED
Power supply

Electrical

60.8919

LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac



REQUIRED
Power supply

Electrical

60.9170

LED power supply source for remote installation, 48V/120W. 220/240 Vac



REQUIRED
Power supply

Electrical

60.9607

LED power supply source for remote installation, 110Vac-135W / 220Vac-200W.



REQUIRED
Component

06.5135.14A

End Cap Dali/1-10V/FLOS Control@ by Casambi compatible



REQUIRED
Component

06.5135.40A

End Cap Dali/1-10V/FLOS Control@ by Casambi compatible



REQUIRED
Component

06.5142.14A

End Cap On board dimmer/FLOS Control@ by Casambi compatible



REQUIRED
Component

06.5142.40A

End Cap On board dimmer/FLOS Control@ by Casambi compatible