

## Electrical Feed Rod Rose Ø 140 mm

Designed by Vincent Van Duysen, 2017



Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling surface     |
| Environments           | Indoor dry location |
| Light sources included | no                  |
| Number of lamps        | 1                   |

### Physical

|             |       |
|-------------|-------|
| Color       | Black |
| Trim        | No    |
| Length (in) | 11.81 |
| IP internal | 20    |



### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Electrical

Emergency type No

### Notes

The closure terminals will also be electrified and must be ordered separately. Rod with a Ø140 connection rose: a supply rod for remote installation of the power supply through the connection rose. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED  
Power supply  
LEDSB60W48V-NDM-D01  
LED Driver, 48VDC, 60W, Non-Dimming, 120-277V



REQUIRED  
Power supply  
Electrical  
LEDSB30W48V-NDM-D01  
LED power supply source for remote installation, 48V/30W



REQUIRED  
Power supply  
LEDSB96W48V-NDM-D01  
LED Driver, 48VDC, 96W, Non-Dimming, 120-277V



REQUIRED  
Component  
06.5135.14A  
End Cap Dali/1-10V/FLOS Control® by Casambi compatible



REQUIRED  
Component  
06.5135.40A  
End Cap Dali/1-10V/FLOS Control® by Casambi compatible



REQUIRED  
Component  
06.5142.14A  
End Cap On board dimmer/FLOS Control® by Casambi compatible



REQUIRED  
Component  
06.5142.40A  
End Cap On board dimmer/FLOS Control® by Casambi compatible