

# FLOS

06.5123.14 Black

## Electrical Feed Rod Rose Ø 50 mm

Designed by Vincent Van Duysen, 2017



Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

|                 |                     |
|-----------------|---------------------|
| Mounting        | Ceiling surface     |
| Environments    | Indoor dry location |
| Icos            | No                  |
| Number of heads | 1                   |

### Physical

|                 |       |
|-----------------|-------|
| Colour          | Black |
| Trim            | No    |
| Length (mm)     | 700   |
| Net weight (kg) | 0.748 |
| IP internal     | 20    |
| IP external     | 20    |



### Download

[Mounting instructions](#)

[↓ PDF](#)



### Electrical

Emergency type No

### Notes

The closure terminals will also be electrified and must be ordered separately. Rod with a Ø50 connection rose: a supply rod for remote installation of the power supply in an accessible place. Adjustable 25 mm, to adapt it to irregular ceilings.

<https://professional.flos.com/en/global/product/electrical-feed-rod-rose-50-mm-06.5123.14/>

06.5123.14

©2022 Flos - P.IVA 00290820174 - 12/12/2023

[professional.flos.com](https://professional.flos.com) | [info@flos.com](mailto:info@flos.com) 1/3

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.



## Accessories & Power Supply



REQUIRED  
Power supply

Electrical

60.8919

LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac



REQUIRED  
Power supply

Electrical

60.9170

LED power supply source for remote installation, 48V/120W. 220/240 Vac



REQUIRED  
Power supply

Electrical

60.9607

LED power supply source for remote installation, 110Vac-135W / 220Vac-200W.



REQUIRED  
Component

06.5135.14A

End Cap Dali/1-10V/FLOS Control@ by Casambi compatible



REQUIRED  
Component

06.5135.40A

End Cap Dali/1-10V/FLOS Control@ by Casambi compatible



REQUIRED  
Component

06.5142.14A

End Cap On board dimmer/FLOS Control@ by Casambi compatible



REQUIRED  
Component

06.5142.40A

End Cap On board dimmer/FLOS Control@ by Casambi compatible