

Electrical Feed suspended Rod 27.56" (700mm)

Length: 27.56 - Suspension



Aircraft cable with mounting hardware 33ft (10m). Feed wire 37.8ft (11.5m)

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Suspension
Environments	Indoor dry location

Physical

Color	White
Length (in)	27.56
Net weight (lb)	1.65
Package volume (in)	2380
IP internal	20



Download

Family spec sheet	ZIP
Mounting instructions	PDF

Electrical

Insulation class	III
Driver	Remote

Accessories & Power Supply



REQUIRED
Power supply
LEDSB60W48V-NDM-D01
LED Driver, 48VDC, 60W, Non-Dimming, 120-277V



REQUIRED
Power supply
Electrical
LEDSB30W48V-NDM-D01
LED power supply source for remote installation, 48V/30W



REQUIRED
Power supply
LEDSB96W48V-NDM-D01
LED Driver, 48VDC, 96W, Non-Dimming, 120-277V



REQUIRED
Component
06.5135.14A
End Cap Dali/1-10V/FLOS Control® by Casambi compatible



REQUIRED
Component
06.5135.40A
End Cap Dali/1-10V/FLOS Control® by Casambi compatible



REQUIRED
Component
06.5142.14A
End Cap On board dimmer/FLOS Control® by Casambi compatible



REQUIRED
Component
06.5142.40A
End Cap On board dimmer/FLOS Control® by Casambi compatible