

FLOS

05.4385.GY.90 Deep Green

Emi Floor NEW


Designed by Erwan Bouroullec, 2023



Anti-glare appliance for installation on tables and coffee tables. Built-in 100-240 V power supply, with cable and plug. Spare parts for the optical module (lens) are available, please see the accessories. Independent control of the Up&Down lighting through Touch Dimming capacitive sensors in the top part of the central rod.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8424229003291
Mounting	Floor
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	47.5
System power (W)	51.5
Source flux (lm)	4801
System flux (lm)	3244

Physical

Color	Deep Green
Orientation	Fixed
Cord color	Black
Cord length (in)	98
Net weight (lb)	32.1
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


ULD	ZIP
LDT / IES	ZIP

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric


Lighting type	Total
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	89
Rg gamut index	101
LED Life / Failure Ratio	L80B50>60.000h @Tc=85°C
Beam angle C0-180 (°)	32
Beam angle C90-270 (°)	32
Extreme cut off	Yes
UGR _L	<16

Electrical

Frequency (Hz)	50/60
Main voltage (Vac)	100-240
LED current (mA)	940
Driver	Integrated
Dimmable	Yes
Dimming range (%)	1-100
Dimming interface	Dimmer Integrated
Plug type	Twist and Lock

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Notes

Gross luminous flux:
UpLigh - 3714 lm
DownLight - 1087 lm
Net luminous flux:
UpLigh - 2559 lm
DownLight - 685 lm The technological heart of Emi combines with an exquisitely crafted base made of cast iron. Imperfections present on the surface of the base are the result of a manual production process that makes each product unique. Class 2 Listed.

Accessories & Power Supply



OPTIONAL
Diffuser
Optical

08.0956.14
3 Lens Kit for Emi Ceiling Large,
Emi Floor & Emi Table - Flood
Optic



OPTIONAL
Diffuser
Optical

08.0956.40
3 Lens Kit for Emi Ceiling Large,
Emi Floor & Emi Table - Flood
Optic