



05.4385.RY Deep Red

Emi Floor


Designed by Erwan Bouroullec, 2023



Anti-glare appliance for installation on the floor. Built-in 220-240 V power supply, with cable and plug. Spare parts for the optical module (lens) are available, please see the accessories. Independent control of the Up&Down lighting through Touch Dimming capacitive sensors in the top part of the central rod.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8424229003314	
Mounting	Floor	
Environments	Indoor dry location	
Light Source Type	LED	
LED type	LED array	
Lamp category	LED	
Number of heads	1	
Power (W)	42.7	
System power (W)	49.5	
Source flux (lm)	4801	
System flux (lm)	3244	

Physical

Colour	Deep Red	
Orientation	Fixed	
Cord colour	Black	
Cord length (mm)	2500	
Net weight (kg)	14.55	
IP internal	20	

Download

Mounting instructions

业 PDF

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

2D <u>♣</u> ZIP
3D <u>♣</u> ZIP









https://professional.flos.com/en/global/product/emi-floor-05.4385.ry/

05.4385.RY

Schematic light drawing



 $\underline{h(m) \quad E(lx) \quad D(m)}$ 57 14 29

3483 cd 45°	
uminous flux luminaire	

1	8483	0.57
2	2121	1.14
3	943	1.72
4	530	2.29
5	339	2.86

Electrical Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	89
Rg gamut index	101
LED Life / Failure Ratio	L80B50>60.000h_Tc85°C
Beam angle C0-180 (°)	32
Beam angle C90-270 (°)	32
Extreme cut off	Yes
UGR _L	<16

Insulation class	III	
Frequency (Hz)	50/60	
Main voltage (Vac)	110-240	
LED current (mA)	940	
Power Supply	Integrated	
Dimmable	Yes	
Dimming range (%)	1-100	
Dimming interface	Dimmer Integrated	
Plug type	Twist and Lock	

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Notes

Gross luminous flux: UpLigh - 3714 lm DownLight - 1087 lm Net luminous flux: UpLigh - 2559 lm DownLight - 685 lm

Accessories & Power Supply



OPTIONAL Diffuser

Optical

08.0956.14

3 Lens Kit for Emi Ceiling Large, Emi Floor & Emi Table - Flood Optic



OPTIONAL Diffuser

Optical

08.0956.40

3 Lens Kit for Emi Ceiling Large, Emi Floor & Emi Table - Flood Optic