

FLOS

FA116274218 Deep Brown

Emma Wall 2 Double Led

NEW


Designed by FLOS Outdoor, 2010



LED source included. Electrical power supply 220-240V ON/OFF. With IP65 cable guide for rubber cables 5mm<ø<10mm and a connection box for fast connections. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793614601
Mounting	Wall
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	9
System power (W)	12
Source flux (lm)	1148
Lumen Output (lm)	784

Physical

Colour	Deep Brown
Orientation	Fixed
Net weight (kg)	1.44
Package height (mm)	135
Package width (mm)	235
Package length (mm)	115
IP internal	66

Download

Mounting instructions [ZIP](#)


Photometric Files

LDT / IES [ZIP](#)


Technical Drawings

2D [ZIP](#)

3D [ZIP](#)



Schematic light drawing



Beam Angle: 55°

h(m)	E(lx)	D(m)
1	444	1.04
2	111	2.08
3	49	3.11
4	28	4.15
5	18	5.19

Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	54
Beam angle C90-270 (°)	54
Beam angle indirect C0-180 (°)	54
Beam angle indirect C90-270 (°)	54
Extreme cut off	No

Electrical


Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	110-240
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL Accessory

F990C040000

2 way terminal block 4 poles
IP68. (ø7÷12mm cable).