



# Emma Wall 2 Mono Led NEW


Designed by FLOS Outdoor, 2010



LED source included. Integrated electrical power supply 220-240V ON/OFF. With IP65 cable guide for rubber cables 5mm<ø<10mm and a connection box for fast connections. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

EAN	8054793614076
Mounting	Wall
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	5
System power (W)	6.5
Source flux (lm)	649
Lumen Output (lm)	488

#### Physical

Colour	Grey
Orientation	Fixed
Net weight (kg)	1.44
Package height (mm)	135
Package width (mm)	235
Package length (mm)	115
IP internal	66

### Download

Mounting instructions

<u>↓</u> ZIP

#### Photometric Files

LDT / IES

₹ ZIP

#### **Technical Drawings**

2D <u>♣</u> ZIP 3D <u>♣</u> ZIP











https://professional.flos.com/en/global/product/emma-wall-2-mono-led-fa1161721206/

FA1161721206

## Schematic light drawing



Bear	Beam Angle:	
h(m)	E(lx)	D(m)
1	4511	0.25
2	1128	0.50
3	501	0.76
4	282	1.01
5	180	1.26

188 lm			

Beam angle C0-180 (°)

Extreme cut off

#### Electrical Photometric

Symmetric

4000 80

14

No

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	110-240
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

# **Ecodesign and Energy** Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

#### **Notes**

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

#### **Accessories & Power Supply**



OPTIONAL Accessory

F990C040000

2 way terminal block 4 poles IP68. (ø7÷12mm cable).