



FA1161722130 Black

# Emma Wall 2 Mono Led NEW

Designed by FLOS Outdoor, 2010




LED source included. Integrated electrical power supply 220-240V ON/OFF. With IP65 cable guide for rubber cables 5mm<ø<10mm and a connection box for fast connections. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use.

Are you a professional and your project needs consulting and support?

005/70261/160

**BOOK AN APPOINTMENT** 



## Main specifications

EAN	8054/93614168	
Mounting	Wall	
Environments	Outdoor wet location	
Light source type	LED	
Light sources included	Yes	
LED type	Power LED	
Number of lamps	1	
Power (W)	5	
System power (W)	6.5	
Source flux (lm)	649	
Lumen Output (lm)	436	

## Physical

Colour	Black
Orientation	Fixed
Net weight (kg)	1.44
Package height (mm)	135
Package width (mm)	235
Package length (mm)	115
IP internal	66

## Download

Mounting instructions

₹ ZIP

### Photometric Files

LDT / IES

**↓** ZIP

## **Technical Drawings**

2D ₹ ZIP **↓** ZIP











https://professional.flos.com/en/global/product/emma-wall-2-mono-led-fa1161722130/

FA1161722130

## Schematic light drawing



Beam Angle:		55°
h(m)	E(lx)	D(m)
1	494	1.04
2	124	2.08
3	55	3.11
4	31	4.15
5	20	5 19

7 527 cd \ 30°	5	20	5.
ous flux <b>l</b> uminaire			

### Photometric

Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	54
Beam angle C90-270 (°)	54
Extreme cut off	No

#### Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	110-240
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

# **Ecodesign and Energy** Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

#### **Notes**

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

## **Accessories & Power Supply**



OPTIONAL Accessory

F990C040000

2 way terminal block 4 poles IP68. (ø7÷12mm cable).