

Find Me 1 Suspension


Designed by Jorge Herrera



The Find Me Suspension is a thin pendant mount fixture. Deep matte black snoot maximizes cut off and reduces glare. Snoot in pendant version can be changed out to add a touch of color. The Find Me line is available as a single and as a pendant.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	6
System flux (lm)	365

Physical

Color	White
Trim	No
Orientation	Adjustable
Net weight (lb)	0.51
Package volume (in)	62
IP internal	20

Download

[Family spec sheet](#) [ZIP](#)

[Mounting instructions](#) [PDF](#)


Photometric Files

[LDT / IES](#) [ZIP](#)

Ecodesign and Energy Labelling



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	14
Beam angle C90-270 (°)	14
UGR _L	<10


Electrical

Insulation class	III
Forward voltage (V)	12
LED current (mA)	500
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Mains Cut Dimming

Notes

Integral LED is not field replaceable. Fixture is constant Current Low Volatge LED, Class 2. Just 1 accessory can be install at the time. For filter options contact Flos. Wiring suitable for plenum spaces The fitting is supplied pre-wired ready to be connected to a remote power supply (not included). The product includes interchangeable shield cylinder in different colours (orange, violet and black) 3500K available, but not cataloged. Consult factory for additional color temperatures.


Accessories & Power Supply



REQUIRED
Power supply

Electrical


SP40W500MA-10V-A02
Splice Box 40W, 1% dim, 0-10V,
500mA 120/277V.



REQUIRED
Power supply

Electrical


SP25W500MA-10V-A01
Splice Box UL 7"x3-5/8"x1-1/4",
500mA , 25W, 0-10V Dimmable,
120-277V



REQUIRED
Power supply

Electrical


SP30W500MA-ELV-U01
Splice Box UL 7"x3-5/8"x1-1/4",
500mA , 30W, ELV Dimmable,
120-277V



REQUIRED
Power supply

Electrical


SP14W500MA-TRI-S01
Splice Box UL 7"x3-5/8"x1-1/4",
Dim Hi-lume 1% 2-Wire LED
Driver 500mA , 14W, 120V



REQUIRED
Power supply


Electrical

SP26W500MA-TRI-S01
Splice Box UL 7"x3-5/8"x1-1/4",
Dim Hi-lume 1% 2-Wire LED
Driver 500mA , 26W, 120V



REQUIRED
Accessory

08U0003.14
Find Me Suspensión Cover Plate
Canopy, Black



REQUIRED
Accessory

08U0003.30
Find Me Suspensión Cover Plate
Canopy, White