

Find Me 1 Suspension


Designed by Jorge Herrera



The Find Me Suspension is a thin pendant mount fixture. Deep matte black snoot maximizes cut off and reduces glare. Snoot in pendant version can be changed out to add a touch of color. The Find Me line is available as a single and as a pendant.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	6
System flux (lm)	344

Physical

Color	White
Trim	No
Orientation	Adjustable
Net weight (lb)	0.51
Package volume (in)	62
IP internal	20

Download

Family spec sheet [ZIP](#)

Mounting instructions [PDF](#)


Photometric Files

LDT / IES [ZIP](#)

Ecodesign and Energy Labelling



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	14
Beam angle C90-270 (°)	14
UGR _L	<10


Electrical

Insulation class	III
Forward voltage (V)	12
LED current (mA)	500
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Mains Cut Dimming

Notes

Integral LED is not field replaceable. Fixture is constant Current Low Voltage LED, Class 2. Just 1 accessory can be install at the time. For filter options contact Flos. Wiring suitable for plenum spaces The fitting is supplied pre-wired ready to be connected to a remote power supply (not included). The product includes interchangeable shield cylinder in different colours (orange, violet and black) 3500K available, but not cataloged. Consult factory for additional color temperatures.


Accessories & Power Supply



REQUIRED
Power supply

Electrical


SP40W500MA-10V-A02
Splice Box 40W, 1% dim, 0-10V,
500mA 120/277V.



REQUIRED
Power supply

Electrical


SP25W500MA-10V-A01
Splice Box UL 7"x3-5/8"x1-1/4",
500mA , 25W, 0-10V Dimmable,
120-277V



REQUIRED
Power supply

Electrical


SP30W500MA-ELV-U01
Splice Box UL 7"x3-5/8"x1-1/4",
500mA , 30W, ELV Dimmable,
120-277V



REQUIRED
Power supply

Electrical


SP14W500MA-TRI-S01
Splice Box UL 7"x3-5/8"x1-1/4",
Dim Hi-lume 1% 2-Wire LED
Driver 500mA , 14W, 120V



REQUIRED
Power supply


Electrical

SP26W500MA-TRI-S01
Splice Box UL 7"x3-5/8"x1-1/4",
Dim Hi-lume 1% 2-Wire LED
Driver 500mA , 26W, 120V



REQUIRED
Accessory

08U0003.14
Find Me Suspensión Cover Plate
Canopy, Black



REQUIRED
Accessory

08U0003.30
Find Me Suspensión Cover Plate
Canopy, White