



Find Me 1 Suspension

Designed by Jorge Herrera, 2018



Accent lighting LED module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module non-dimmable. To individually control the lights, select integrated Casambi versions.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

%333 3000

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	5.5
Source flux (lm)	485
Lumen Output (lm)	193
Efficacy (lm/W)	36

Physical

Colour	White
Trim	No
Orientation	Fixed
Spot diameter (mm)	33
Net weight (kg)	0.27
IP internal	20

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	₹ ZIP
3D	↓ ZIP
₿Bim	⊥ ZIP

Schematic light drawing



Beam Angle:		20
h(m)	E(lx)	D(n
1	1285	0.3
2	321	0.7
3	143	1.0
4	80	1.4
5	51	1.7

Beam Angle:		20
h(m)	E(lx)	D(n
1	1285	0.3
2	321	0.7
3	143	1.0
4	80	1.4
_	E 1	17

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	20
Beam angle C90-270 (°)	20
Extreme cut off	No
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	400
Power supply	Remote excluded
Dimmable	No
Power supply type	Non Dimmable

Notes

Accessories included (honeycomb and screening crosspiece).