

# FLOS

09.3707.14C Black

## Find Me 2 (Trim/No Trim)

Designed by Jorge Herrera, 2015



Recessed adjustable luminaire for indoor application. Remote power supply not included.

Are you a professional and your project needs consulting and support?



BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 10                  |
| Source flux (lm)       | 915                 |
| Lumen Output (lm)      | 693                 |

### Physical

|                          |            |
|--------------------------|------------|
| Colour                   | Black      |
| Orientation              | Adjustable |
| Rotation (°)             | 360        |
| Longitudinal tilting (°) | 70         |
| Recessed depth (mm)      | 210        |
| Net weight (kg)          | 0.59       |
| IP internal              | 20         |



### Download

Mounting instructions [Download PDF](#)

### Photometric Files


LDT / IES [Download ZIP](#)

### Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)

Bim [Download ZIP](#)




### Ecodesign and Energy Labelling



Replaceable (LED only)  
light source by a  
professional

Schematic light drawing



Photometric

|                          |                             |
|--------------------------|-----------------------------|
| Lighting type            | Direct                      |
| Light distribution       | Symmetric                   |
| CCT (K)                  | 2700                        |
| CRI>                     | 90                          |
| Rf fidelity index        | 90                          |
| Rg gamut index           | 99                          |
| LED Life / Failure Ratio | L80B20 >36000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 18                          |
| Beam angle C90-270 (°)   | 18                          |
| UGR <sub>L</sub>         | <10                         |

Electrical

|                     |                                                                                                |
|---------------------|------------------------------------------------------------------------------------------------|
| Insulation class    | III                                                                                            |
| Forward voltage (V) | 12                                                                                             |
| LED current (mA)    | 850                                                                                            |
| Power supply        | Remote excluded                                                                                |
| Dimmable            | Yes                                                                                            |
| Power supply type   | Non Dimmable,<br>Dimmable DALI 2,<br>Dimmable 0-10V,<br>Dimmable Casambi,<br>Mains Cut Dimming |

Notes

Accessories included (honeycomb and screening crosspiece). Remote power supply to be installed in an accessible place. Ceiling thickness between 8 and 30mm.

Accessories & Power Supply



REQUIRED  
Power supply  
Electrical

60.8530  
Continuous current power supply of 25-50W, 110/240V - 50/60Hz with power current selected through adjustable 350mA - 25W /500mA - 35W/ 700mA - 50W /750mA - 54W /900/ 1050 mA - 60W switch. Dali 2, 0/1-10V or push dimming



REQUIRED  
Power supply  
Electrical

60.8911  
Non dimmable continuous current power supply of 15-20W, 110/240V - 50/60Hz, with power current selected through adjustable 350 mA-15W /500 mA/ /550 / 700 / 850 mA / 900 mA - 20W switch



REQUIRED  
Power supply  
Electrical

60.9162  
Continuous current power supply 220/240V - 50/60Hz. Adjustable Current 300mA-13W / 350mA-15W / 400mA-18W / 450mA-20W / 500mA-22W / 550mA-24W / 600mA-27W / 650mA-29W / 700mA-31W / 750mA-32W / 800mA-33W / 850mA-35W / 900mA-38W / 950mA-40W / 1000/1050mA-4...



REQUIRED  
Power supply  
Electrical

60.8529A  
Continuous current power supply of 10W, 110V / 12W, 240V - 50/60Hz with 700 mA supply voltage



REQUIRED  
Power supply  
Electrical

60.7678



REQUIRED  
Power supply  
Electrical

60.9207



REQUIRED  
Power supply  
Electrical

60.9467

|                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                          |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Continuous current supply<br>source of 240V - 50/60Hz with<br>dimmable Dali 2, Push dimming.<br>150mA - 7.8W / 200mA - 10.4W /<br>250mA - 13W / 300mA - 15.6W /<br>350mA - 18.2W / 400mA - 20.8W<br>/ 500mA - 26W / 600mA - 31.2W<br>/ 700mA - 36.4W / 750mA - 39W<br>/ 800mA - 41.6... | Casambi continuous current<br>power supply, dimmable<br>220/240V - 50/60Hz, 300mA -<br>16W / 350mA - 18,5W / 400mA -<br>21,5W / 450 mA - 24W / 500mA -<br>27W / 600mA - 32W / 650 mA -<br>35W / 700 mA - 36W /750 /800<br>/900 /1000 /1050 /1200 mA -<br>38W. | Mains dimming 20W Constant<br>current power supply, AC phase-<br>cut adjustable, trailing & leading<br>edge dimming, 220/240V -<br>50/60Hz, with dip-switch<br>programmable power supply<br>current. Output current: 900mA -<br>20W / 850mA - 20W / 800mA -<br>20W / 750mA - 20W / 70... |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|