

FLOS

09.2125.40B White

Fort Knox Wall LED Mini

Designed by Philippe Starck




LED - Power LED - 21W - 1972lm - 3000K - CRI> 90 - Beam° 32

Wall-mounted LED luminaire for indirect lighting. Power source incorporated into luminaire's body.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Wall surface
Environments	Indoor dry location
Light Source Type	LED
LED type	Power LED
Lamp category	LED
Number of heads	1
Power (W)	21
System power (W)	25
Source flux (lm)	2718
System flux (lm)	1972

Physical

Colour	White
Trim	No
Orientation	Fixed
Length (mm)	150
Net weight (kg)	0.6
Package height (mm)	23
Package width (mm)	23
Package length (mm)	7
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



Schematic light drawing



Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50 50.000h
Beam angle C0-180 (°)	32
Beam angle C90-270 (°)	88
Extreme cut off	No
UGR _L	<16


Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power Supply	Integrated
Dimmable	No
Power Supply Type	Non Dimmable

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional