

# FLOS

09.2125.40B White

## Fort Knox Wall LED Mini

Designed by Philippe Starck




LED - Power LED - 21W - 1972lm - 3000K - CRI> 90 - Beam° 32

Wall-mounted LED luminaire for indirect lighting. Power source incorporated into luminaire's body.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Wall surface
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	21
System power (W)	25
Source flux (lm)	2718
System flux (lm)	1972

### Physical

Colour	White
Trim	No
Orientation	Fixed
Length (mm)	150
Net weight (kg)	0.6
Package height (mm)	23
Package width (mm)	23
Package length (mm)	7
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)


[Bim](#) [↓ ZIP](#)



## Schematic light drawing



## Ecodesign and Energy Labelling



Replaceable (LED only)  
light source by a  
professional



Replaceable control  
gear by a professional

## Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50 50.000h
Beam angle C0-180 (°)	32
Beam angle C90-270 (°)	88
Extreme cut off	No
UGR <sub>L</sub>	<16

## Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable