

FLOS

09.2125.40BDM White

Fort Knox Wall LED Mini Mains Dimming Version

NEW

Designed by Philippe Starck, 2022




LED - Power LED - 21W - 1972lm - 3000K - CRI> 90 - Beam° 32

Wall-mounted LED luminaire for indirect lighting. Power source incorporated into luminaire's body.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Wall surface
Environments	Indoor dry location
Light Source Type	LED
LED type	Power LED
Lamp category	LED
Number of heads	1
Power (W)	21
System power (W)	25
Source flux (lm)	2718
System flux (lm)	1972

Physical

Colour	White
Trim	No
Orientation	Fixed
Length (mm)	150
Net weight (kg)	0.6
Package height (cm)	23
Package width (cm)	23
Package length (cm)	7
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



Schematic light drawing




Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50 50.000h
Beam angle C0-180 (°)	32
Beam angle C90-270 (°)	88
UGR _L	11


Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Driver	Integrated
Dimmable	Yes
Dimming type	Mains Cut Dimming

Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional