

FLOS

09.2126.14.DM Black

Fort Knox Wall LED Mini Mains Dimming Version

NEW

Designed by Philippe Starck, 2022




LED - Power LED - 22W - 1440lm - 2700K - CRI> 90 - Beam° 32

Wall-mounted LED luminaire for indirect lighting. Power source incorporated into luminaire's body.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

| | |
|-------------------|---------------------|
| Mounting | Wall surface |
| Environments | Indoor dry location |
| Light Source Type | LED |
| LED type | Power LED |
| Lamp category | LED |
| Number of heads | 1 |
| Power (W) | 22 |
| System power (W) | 25 |
| Source flux (lm) | 1985 |
| System flux (lm) | 1440 |

Physical

| | |
|---------------------|-------|
| Colour | Black |
| Trim | No |
| Orientation | Fixed |
| Length (mm) | 150 |
| Net weight (kg) | 0.6 |
| Package height (cm) | 23 |
| Package width (cm) | 23 |
| Package length (cm) | 7 |
| IP internal | 20 |

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



Schematic light drawing



Photometric

| | |
|--------------------------|----------------|
| Lighting type | Indirect |
| Light distribution | Asymmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| LED Life / Failure Ratio | L80B50 50.000h |
| Beam angle C0-180 (°) | 32 |
| Beam angle C90-270 (°) | 88 |

Electrical

| | |
|--------------------|-------------------|
| Insulation class | I |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| Driver | Integrated |
| Dimmable | Yes |
| Dimming type | Mains Cut Dimming |

Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional