



Franco 2 CoB Led Symmetric Optic NEW

Designed by FLOS Outdoor, 2007






LED source included. Integrated electrical power supply 220-240V ON/OFF. Graduated fixing bracket included. Equipped with a M20x1.5 cable guide (for 7mm<ø<13mm cables) and IP68 connector. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use. Optional accessories: posts and arms for mast mounting.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793698410
Mounting	Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	39
System power (W)	43
Source flux (lm)	5560
Lumen Output (lm)	3465

Physical

Colour	vvnite
Orientation	Adjustable
Longitudinal tilting (°)	113
Net weight (kg)	4,22
Package height (mm)	145
Package width (mm)	260
Package length (mm)	430
Package volume (m3)	0.02
IP internal	65

Download

Mounting instructions

₹ ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

2D 🛂 ZIP 3D **↓** ZIP











https://professional.flos.com/en/global/product/franco-2-cob-led-symmetric-optic-fa962821301.a/

FA962821301.A

Schematic light drawing



Bean	Beam Angle:	
h(m)	E(lx)	D(m)
1	2370	1.74
2	593	3.48
3	263	5.22
4	148	6.97
5	95	8 71

Luminous flux luminaire 3465 lm

Photometric

Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	80
Beam angle C90-270 (°)	80
Extreme cut off	No

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Dimming interface	Not Dimmable
Emergency	No

Electrical

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply









OPTIONAL Accessory

F990E00A000

S.P.D. (SURGE PROTECTION DEVICE)

OPTIONAL Accessory

FA116

Base Plate and Fixing Bolts for Pole Ø 102 mm h 4000/5000 mm with Base

OPTIONAL Bracket

FA11433

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 180 mm Double

OPTIONAL Bracket

FA11406

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 180 mm Double









OPTIONAL Bracket

FA11533

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 500 mm Double

OPTIONAL Bracket

FA11506

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 500 mm Double

OPTIONAL Bracket

FA11233

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 180 mm Single

OPTIONAL Bracket

FA11206

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 180 mm Single









OPTIONAL Bracket

FA11333

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 500 mm Single

OPTIONAL Bracket

FA11306

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 500 mm Single

OPTIONAL Pole

FA24806

Pole Ø76 mm h 3500 mm(with Base)

OPTIONAL Pole

FA24833

Pole Ø76 mm h 3500 mm(with Base)



OPTIONAL Pole

FA25006

Pole Ø76 mm h 3500 mm (+500 mm In-ground)



OPTIONAL Pole

EVSEUSS

Pole Ø76 mm h 3500 mm (+500 mm In-ground)



OPTIONAL Pole

FA24906

Pole Ø76 mm h 4500 mm(with Base)



OPTIONAL Pole

FA24933

Pole Ø76 mm h 4500 mm(with Base)



OPTIONAL Pole

FA414006

Pole Ø 102 mm h 4000 mm With Base



OPTIONAL Pole

FA414033

Pole Ø 102 mm h 4000 mm With Base



OPTIONAL Pole

FA41450

Pole Ø 102 mm h 4000 mm (+500 mm In-ground)



OPTIONAL Pole

FA414533

Pole Ø 102 mm h 4000 mm (+500 mm In-ground)



OPTIONAL Pole

FA415006

Pole Ø 102 mm h 5000 mm With Base



OPTIONAL Pole

FA415033

Pole Ø 102 mm h 5000 mm With Base



OPTIONAL Pole

FA415506

Pole Ø 102 mm h 5000 mm (+500 mm In-ground)



OPTIONAL Bracket

A9033

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 180 mm Double









OPTIONAL Bracket

FA9006

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 180 mm Double

OPTIONAL Bracket

A9533

Pole Bracket Franco 2/Perseo 4 Ø 60 mm 180 mm Double

OPTIONAL Bracket

FA9506

Pole Bracket Franco 2/Perseo 4 Ø 60 mm 180 mm Double

OPTIONAL Bracket

FA8933

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 500 mm Double









OPTIONAL Bracket

FA8906

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 500 mm Double

OPTIONAL Bracket

FA9633

Pole Bracket Franco 2/Perseo 4 Ø 60 mm 500 mm Double

OPTIONAL Bracket

FA9606

Pole Bracket Franco 2/Perseo 4 Ø 60 mm 500 mm Double

OPTIONAL Bracket

FA9333

Pole Bracket Franco 2/Perseo 4 Ø 60 mm 180 mm









OPTIONAL Bracket

FA9306

Pole Bracket Franco 2/Perseo 4 Ø 60 mm 180 mm

OPTIONAL Bracket

FA9433

Pole Bracket Franco 2/Perseo 4 Ø 60 mm 500 mm

OPTIONAL Bracket

FA9406

Pole Bracket Franco 2/Perseo 4 Ø 60 mm 500 mm

OPTIONAL Bracket

FA7833

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 180 mm Single









OPTIONAL Bracket

FA7806

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 180 mm Single

OPTIONAL Bracket

FA7933

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 500 mm Single

OPTIONAL Bracket

FA7906

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 500 mm Single

OPTIONAL Pole

FA25106

Pole Ø76 mm h 4500 mm (+500 mm In-ground)



FA25133

Pole Ø76 mm h 4500 mm (+500 mm In-ground)