

# FLOS

09.3201.BZA9S Bronze

## G-O Amber Light


Designed by Jorge Herrera



G-O is a family of small lights that make a big impression while providing useful illumination for stairs, paths and way finding, while only using 1.2 watts per fixture. Robust machined bronze, stainless steel or aluminum construction available in a variety of finishes and light color options result in a lighting tool that enhances the most refined architecture.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Wall recessed       |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 1.2                 |
| Source flux (lm)       | 96                  |
| System flux (lm)       | 2                   |

### Physical

|                     |        |
|---------------------|--------|
| Color               | Bronze |
| Trim                | Yes    |
| Orientation         | Fixed  |
| Recessed depth (in) | 2.2    |
| Net weight (lb)     | 0.45   |
| Package volume (in) | 62     |
| IP internal         | 65     |

### Download

Family spec sheet [ZIP](#)


Mounting instructions [PDF](#)

### Photometric Files

LDT / IES [ZIP](#)



Schematic light drawing



Photometric

|                        |                  |
|------------------------|------------------|
| Lighting type          | Indirect, Direct |
| Light distribution     | Symmetric        |
| CCT (K)                | 3000             |
| Beam angle C0-180 (°)  | 72               |
| Beam angle C90-270 (°) | 72               |
| UGR <sub>L</sub>       | <16              |


Electrical

|                     |                 |
|---------------------|-----------------|
| Insulation class    | III             |
| Forward voltage (V) | 24              |
| LED current (mA)    | 25              |
| Driver              | Remote excluded |

Notes


Optional extruded aluminum accessory for embedding in concrete walls installations available. Fixture can be wired in paralel, up to maximum allowed wattage of power supply Distance should not exceed driver’s limits for voltage drop.

Accessories & Power Supply



REQUIRED  
Power supply

LEDSB30W24V-10V-D1  
LED Driver, 30W, 120-277Vac, 0-10V dimming driver



OPTIONAL  
Power supply

LEDSB60W24V-VAR-Y1  
LED Driver, 24VDC, 60W, Variable dim Triac, 0-10V Dimming PWM, 120-277Vac , indoor-outdoor enclosure



OPTIONAL  
Accessory

08.8422.00  
Prepared for recessing