

FLOS

SA.5102.1A Lighting blue

G-O IN

Designed by Jorge Herrera, 2017




LED - Top LED - 1.2W - 3000K - Beam° 117

Recessed sign luminaire for indoor application. Power supply source not included: electronic transformer with constant voltage (24V) for LED. 220/240V, 50/60Hz. It includes 1000mm power supply cable.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Wall recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Power (W)	1.2
Source flux (lm)	105

Physical

Colour	Lighting blue
Trim	No
Orientation	Fixed
Net weight (kg)	0.7
IP internal	20
IP external	20

Download

Mounting instructions

PDF




Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	3000
Beam angle C0-180 (°)	117
Beam angle C90-270 (°)	117
UGR _L	<16

Electrical

Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	No
Power supply type	Non Dimmable
Emergency	No

Accessories & Power Supply



REQUIRED
Power supply
Electrical

60.9157
Electronic transformer with
constant voltage (24V) for LED.
8W, 110/240V, 50/60H



REQUIRED
Power supply
Electrical

60.8703
Electronic transformer with
constant voltage (24V) for LED.
100/240V, 25W



REQUIRED
Accessory
Electrical

60.8640
Control Unit 1-10V



REQUIRED
Accessory
Electrical

60.9766
Control Unit DALI



OPTIONAL
Power supply
Electrical

60.8079
Electronic transformer with
constant voltage (24V) for LED.
8W, 220/240V, 50/60H