

FLOS


09.8401.DY Matte White

Gustave Hospitality

Designed by Vincent Van Duysen, 2022



Gustave is a portable, self-powered luminaire, specially designed for tabletop lighting applications and other related uses as supplementary lighting. Gustave's compact size encloses a perfect mix of the most innovative optical and light technology and a disruptive engineering, developed in the service of a discretionary purpose of Flos for this project: to create the first portable luminaire on the market with circular design awareness, ecological and honestly conceived against obsolescence. Portable luminaire with autonomous battery, designed for hospitality (hotels, restaurants...). Powered by 'Button Type 18650 Li-Ion' batteries (3 units, not included). External battery charger, not included. 3-Step dimming (25%, 50%, 100%) by means of capacitive haptic push button.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Table
LED type	Top LED
Lamp category	LED
Number of heads	1
Power (W)	2.3
System power (W)	2.3
Source flux (lm)	235
System flux (lm)	169
Efficacy (lm/W)	73

Physical

Colour	Matte White
Length (mm)	155
Net weight (kg)	0.67
Package height (mm)	35
Package width (mm)	20
Package length (mm)	20
Package volume (m3)	0.02
IP internal	54

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)



Ecodesign and Energy Labelling




Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Schematic light drawing



Beam Angle: 145°

h(m)	E(lx)	D(m)
1	24	6.28
2	6	12.56
3	3	18.84
4	1	25.11
5	1	31.39

Luminous flux Luminaire
169 lm

Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	93
Rg gamut index	100
Beam angle C0-180 (°)	144
Beam angle C90-270 (°)	144

Electrical

Insulation class	III
LED voltage Vf (Vdc)	11,1
LED current (mA)	120
Dimmable	Yes
Dimming type	Dimmable
Dimming interface	Dimmer Integrated
Batteries inside	No
Battery type	LI-IO

Notes

Product Battery autonomy: 100% - 12 hours / 50% - 24 hours / 25% - 48 hours.
Batteries 3xLi-Ion 18650 2600mAh not included

Accessories & Power Supply



REQUIRED
Accessory

Electrical

08.0745.00

Pack 3x Battery for Gustave
Hospitality



REQUIRED
Accessory

Electrical

08.0746.00

Pack 6x Battery for Gustave
Hospitality



REQUIRED
Accessory

Electrical

08.0747.00

Pack 12x Battery for Gustave
Hospitality



REQUIRED
Accessory

Electrical

08.0748.00

Pack 24x Battery for Gustave
Hospitality



REQUIRED
Accessory

Electrical

60.9848

Lithium battery charger



REQUIRED
Accessory

Electrical

08.0958.00

UK Lithium battery charger