



09.8406.GX Lacquered Green

Gustave Residential

Designed by Vincent Van Duysen, 2022



Gustave is a portable, self-powered luminaire, specially designed for tabletop lighting applications and other related uses as supplementary lighting. Gustave's compact size encloses a perfect mix of the most innovative optical and light technology and a disruptive engineering, developed in the service of a discretionary purpose of Flos for this project: to create the first portable luminaire on the market with circular design awareness, ecological and honestly conceived against obsolescence. Portable luminaire with autonomous battery, designed for residential applications. Powered by 'Button Type 18650 Li-Ion' batteries (2 units, included inside the product). USB-C charging cable (plug adapter not included). 0-100% sequential regulation by means of capacitive haptic push button.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Table	
Light source type	LED	
Light sources included	Yes	
LED type	Top LED	
Lamp category	LED	
Number of lamps	1	
Power (W)	2.5	
System power (W)	2.5	
Source flux (lm)	235	
Lumen Output (lm)	169	
Efficacy (Im/W)	73	

Physical

Colour	Lacquered Green
Length (mm)	155
Cord colour	Black
Cord length (mm)	1200
Net weight (kg)	0.78
Package height (mm)	36
Package width (mm)	21
Package length (mm)	21
Package volume (m3)	0.02
IP internal	54



Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings


2D



¥ ZIP

Ecodesign and Energy Labelling







Replaceable control gear by an end-user

https://professional.flos.com/en/global/product/gustave-residential-09.8406.gx/

09.8406.GX











Schematic light drawing



Beam Angle:		145
h(m)	E(lx)	D(n
1	24	6.2
2	6	12.5
3	3	18.8
4	1	25.1
5	1	31.3

Lumin	OUS 1	flux	lumin.	aire
169 lm	ous	iiux	ia i i i i i	unc

Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	93
Rg gamut index	100
Beam angle C0-180 (°)	144
Beam angle C90-270 (°)	144
Extreme cut off	No

Electrical

Insulation class	III
LED current (mA)	180
Dimmable	Yes
Power supply type	Dimmable
Dimming interface	Dimmer Integrated
Plug type	Type A
Batteries inside	Yes
Battery type	LI-IO
Charging cycles guaranteed	500
Charging max power	1 A
Charging min time	5.5
Charging socket/connector	USB-C

Notes

Product Battery autonomy: 100% - 6 hours / 50% - 10 hours / 25% - 18 hours. Batteries included. USB-A / USB-C Cable included. Adapter 5V, min 2A not included.

Accessories & Power Supply



REQUIRED

RF25965

Adapter 5V. Min 2A | EUR USA UK




REQUIRED

RF27576

Gaku Adapter 5V. Min 2A. EUR / USA / UK

Spare Parts



01.	Pack 2x Battery for Gustave	08.0744.00
	Residential	
02.	Cable for Gustave Residential	08.0761.14
	USB-A/USB-C	
02.	Cable for Gustave Residential	08.0761.30
	USB-A/USB-C	





08 07/// 0/

Pack 2x Battery for Gustave Residential



Cable

08 0761 14

Cable for Gustave Residential USB-A/USB-C



Cable

08.0761.30

Cable for Gustave Residential USB-A/USB-C