



09.8406.GX Lacquered Green

Gustave Residential


Designed by Vincent Van Duysen, 2022



Thanks to the particular lighting diffusion technology, the table rechargeable lamp perfectly lights up a wide surface stretching up to a meter. Powered by batteries (included inside the product). Charging by USB-C cable, included. Sequential dimming 0-100%. Gustave is the first luminaire to incorporate a system of exclusive, patented by Flos, asymmetrical emission lenses, arranged in revolution and spanning 360° around the position of the lamp.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Table
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	2.5
System power (W)	2.5
Source flux (lm)	235
System flux (lm)	169
Efficacy (lm/W)	73

Physical

Color	Lacquered Green	
Cord color	Black	
IP internal	54	

	1 715
Family spec sheet	<u>↓</u> ZIF
Mounting instructions	₹ PDF
Photometric Files	
LDT / IES	J. ZIF
Technical Drawings	
recillical blawings	
2D	₹ ZIF
3D	↓ 71F











https://professional.flos.com/en-US/us/product/gustave-residential-09.8406.gx/

09.8406.GX

Schematic light drawing



Beam Angle:		145
h(m)	E(lx)	D(m
1	24	6.2
2	6	12.5
3	3	18.8
4	1	25.1
_	1	21 2

Luminous flux luminaire

Beam Angle:		145
h(m)	E(lx)	D(r
1	24	6.2
2	6	12.5
3	3	18.8
4	1	25.1
5	1	31 3

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	93
Rg gamut index	100
Beam angle C0-180 (°)	144
Beam angle C90-270 (°)	144
Extreme cut off	No

Electrical

Insulation class	III
LED current (mA)	180
Dimmable	Yes
Dimming type	Dimmable
Dimming interface	Dimmer Integrated
Plug type	Type A
Batteries inside	Yes
Battery type	LI-IO
Charging cycles guaranteed	500
Charging max power	1 A
Charging min time	5.5
Charging socket/connector	USB-C

Notes

Product Battery autonomy: 100% - 6 hours / 50% - 10 hours / 25% - 18 hours. Batteries included. USB-A / USB-C Cable included. Adapter 5V, min 2A not included.

Accessories & Power Supply



REQUIRED

RF25965

Adapter 5V. Min 2A | EUR USA UK




REQUIRED

RF27576

Gaku Adapter 5V. Min 2A. EUR / USA / UK

Spare Parts



01.	Pack 2x Battery for Gustave	08.0744.00
	Residential	
02.	Cable for Gustave Residential	08.0761.14
	USB-A/USB-C	
02.	Cable for Gustave Residential	08.0761.30
	USB-A/USB-C	





08 0744 00

Pack 2x Battery for Gustave Residential



Cable

08 0761 14

Cable for Gustave Residential USB-A/USB-C



Cable

08.0761.30

Cable for Gustave Residential USB-A/USB-C