

FA50904301 White

# **Heavy Metal Spot 2** NEW


Designed by FLOS Outdoor



LED source included. Electric remote 24V dc ON/OFF power supply to be ordered separately. Wall fixing bracket included. The luminaire is equipped with a protruding, neoprene, 250 mm cable and a wiring kit with crimp connectors and adhesive heatshrink tubing guaranteeing the water tightness of the connection. Extra clear transparent glass.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



# Main specifications

EAN	8054793627946	
Mounting	Ground	
Environments	ts Outdoor wet location	
LED type	Power LED	
Power (W)	5	
System power (W)	5.9	
Source flux (lm)	466	
Lumen Output (lm)	389	

# Physical

Colour	wnite
Orientation	Adjustable
Longitudinal tilting (°)	180
Net weight (kg)	0.94
Package height (mm)	140
Package width (mm)	180
Package length (mm)	135
IP internal	65

#### Download

Mounting instructions

<u>↓</u> ZIP

# Photometric Files

LDT / IES

₹ ZIP

# **Technical Drawings**

2D	<u>↓</u> ZIP
3D	<b>↓</b> ZIP












# Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F

https://professional.flos.com/en/global/product/heavy-metal-spot-2-fa50904301/

FA50904301

# Schematic light drawing



Bean	Beam Angle:	
h(m)	E(lx)	D(m)
1	3536	0.25
2	884	0.51
3	393	0.76
4	221	1.02
5	1/11	1 27

Luminous flux luminaire

#### Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	14
Beam angle C90-270 (°)	14
Extreme cut off	No

#### Electrical

Insulation class	III
Main voltage (Vac)	24
Power supply	Remote excluded
Power supply type	Non Dimmable
Emergency	No

#### Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance' Dimmable version on request

## **Accessories & Power Supply**



OPTIONAL Accessory

FA136

Ground Spike Aimer 1/Aimer 2/Aimer 3/Perseo 2



## OPTIONAL Power supply

RF25747

Power supply 24V 10W /110-240V IP20 Class II selv. Non Dimmable



#### OPTIONAL Power supply

RF25752

Power supply 24Vdc 20W / 220-240V IP67 Class II selv. Non Dimmable



## OPTIONAL Power supply

RF25757

Power supply 24V 10W / 110-240V IP67 Class II selv.\_Non Dimmable



# OPTIONAL Power supply

F990B23AZ00

Power supply 24Vdc 35W /120-270V IP67 Class II selv.



# OPTIONAL Power supply

F990B27A000

Power supply 24Vdc 70W / 220-240V IP67 Class I selv. Non Dimmable



# OPTIONAL Power supply

F990B28A000

Power supply 24Vdc 50W / 220-240V IP67 Class I selv. Non Dimmable