



FA50905312 Forest Green

Heavy Metal Spot 2 NEW


Designed by FLOS Outdoor, 2011



LED source included. Electric remote 24V dc ON/OFF power supply to be ordered separately. Wall fixing bracket included. The luminaire is equipped with a protruding, neoprene, 250 mm cable and a wiring kit with crimp connectors and adhesive heat-shrink tubing guaranteeing the water tightness of the connection. Extra clear transparent glass.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793628325	
Mounting	Ground	
Environments	Outdoor wet location	
Light source type	LED	
Light sources included	Yes	
LED type	Power LED	
Number of lamps	1	
Power (W)	5	
System power (W)	5.9	
Source flux (lm)	466	
Lumen Output (lm)	357	

Physical

Colour	Forest Green	
Orientation	Adjustable	
Longitudinal tilting (°)	180	
Net weight (kg)	0.94	
Package height (mm)	140	
Package width (mm)	180	
Package length (mm)	135	
IP internal	65	

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	业 ZIP
3D	⊥ ZIP

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F**





Non-replaceable light source












IK 07

https://professional.flos.com/en/global/product/heavy-metal-spot-2-fa50905312/

FA50905312

Schematic light drawing



Beam Angle:		53°
h(m)	E(lx)	D(m)
1	431	1.00
2	108	2.00
3	48	3.00
4	27	4.01
5	17	5.01

Luminous flux luminaire 357 lm

Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	54
Beam angle C90-270 (°)	54
Extreme cut off	No

Electrical

Insulation class	III	
Frequency (Hz)	50/60	
Main voltage (Vac)	24	
Power supply	Remote excluded	
Dimmable	No	
Power supply type	Non Dimmable	
Dimming interface	Not Dimmable	
Emergency	No	

Notes

Dimmable version on request

Accessories & Power Supply









REQUIRED Power supply

F990B27A000

Power supply 24Vdc 70W / 220-240V IP67 Class I selv. Non Dimmable REQUIRED
Power supply

F990B28A000

Power supply 24Vdc 50W / 220-240V IP67 Class I selv. Non Dimmable REQUIRED Power supply

RF25747

Power supply 24V 10W /110-240V IP20 Class II selv. Non Dimmable

REQUIRED Power supply

RF25757

Power supply 24V 10W / 110-240V IP67 Class II selv._Non Dimmable



REQUIRED Power supply

RF25752

Power supply 24Vdc 20W / 220-240V IP67 Class II selv. Non Dimmable



REQUIRED
Power supply

F990B23AZ00

Power supply 24Vdc 35W /120-270V IP67 Class II selv.



OPTIONAL Accessory

FA136

Ground Spike Aimer 1/Aimer 2/Aimer 3/Perseo 2