

FLOS


FA52700206 Grey

Hyperion NEW

Designed by FLOS Outdoor, 2012



Hyperion 230V. LED source included. Electrical power supply 220-240V ON/OFF. Equipped with a 200 mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Optional accessories: satin aluminum reflector to increase the luminous flux; 500mm tall, extruded post for the bollard version. Anchor plate to be recessed with mortar needs to be ordered separately.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8054793648972
Mounting	Wall
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	6
System power (W)	10
Source flux (lm)	835
Lumen Output (lm)	442

Physical

Colour	Grey
Orientation	Fixed
Net weight (kg)	0.88
Package height (mm)	245
Package width (mm)	175
Package length (mm)	35
IP internal	65

Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP


Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Schematic light drawing



Photometric





Light distribution	Asymmetric
CCT (K)	4000
CRI>	80
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply

<div><div><div><div>FA160</div><div></div></div><div><div>+</div></div><div><div>Lamp. 4</div><div></div></div><div><div>=</div></div><div><div>+20% lm</div><div></div></div></div><div><div>OPTIONAL</div><div>Accessory</div><div>FA160</div><div>Satin Aluminium Carter Hyperion</div></div></div>	<div><div><div></div></div><div><div>OPTIONAL</div><div>Accessory</div><div>FA247</div><div>Base Plate and Fixing Bolts Hyperion pole</div></div></div>	<div><div><div></div></div><div><div>OPTIONAL</div><div>Accessory</div><div>FA24506</div><div>Pole Hyperion h 500 mm</div></div></div>	<div><div><div></div></div><div><div>OPTIONAL</div><div>Accessory</div><div>F990E00A000</div><div>S.P.D. (SURGE PROTECTION DEVICE)</div></div></div>
--	---	--	--