



FA1022290030 Black

Hyperion Mini NEW




Designed by FLOS Outdoor, 2012



LED source included. Completed with a reflective screen. Remote electrical power supply 24V dc to be ordered separately. Optional junction box to be ordered separately (3 module electrical box, model 503). Equipped with a 250 mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Dimmable.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054/93605999	
Mounting	Wall	
Environments	Outdoor wet location	
Light source type	LED	
Light sources included	Yes	
LED type	Power LED	
Number of lamps	1	
Power (W)	2	
System power (W)	1.9	
Source flux (lm)	156	
Lumen Output (lm)	64	

Physical

Colour	Black
Orientation	Fixed
Net weight (kg)	0.16
Package height (mm)	134
Package width (mm)	70
Package length (mm)	83
IP internal	65

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	⊥ ZIP
3D	<u>↓</u> ZIP

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

















08

https://professional.flos.com/en/global/product/hyperion-mini-fa1022290030/

FA1022290030

Schematic light drawing



Beam Angle:		50°
h(m)	E(lx)	D(m)
1	52	1.19
2	13	2.38
3	6	3.57
4	3	4.75
5	2	5.94

Luminous flux luminaire 64 lm

Photometric

Light distribution	Asymmetric
CCT (K)	4000
CRI>	80
Extreme cut off	No

Electrical

Insulation class	III	
Main voltage (Vac)	24	
Power supply	Remote excluded	
Dimmable	Yes	
Power supply type	Non Dimmable, Dimmable 1-10V, Dimmable DALI 1	
Dimming interface	Remote Dimmable (Dimmer Not Included)	
Emergency	No	

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply









OPTIONAL Power supply

F990B27A000

Power supply 24Vdc 70W / 220-240V IP67 Class I selv. Non Dimmable

OPTIONAL Power supply

F990B28A000

Power supply 24Vdc 50W / 220-240V IP67 Class I selv. Non Dimmable

OPTIONAL Power supply

F990B29A00

Power supply 24Vdc 100W / 220-240V IP67 Class I selv.Non Dimmable

OPTIONAL Power supply

RF2574

Power supply 24V 10W /110-240V IP20 Class II selv. Non Dimmable









OPTIONAL Power supply

RF25750

Power supply 24Vdc 17W / 110-240V (15W@110V) IP20 Class II selv. Dimmable Push-Dimm Or 1.10V

OPTIONAL Power supply

RF25748

Power supply dual function Vout 24Vdc: 8W/100÷240V lout 350ma: 6x1W/100÷240V IP65 Class II selv. Non Dimmable

OPTIONAL Power supply

F990B21A000

Power supply 17W/110÷240V -24Vdc (15W@110V) IP67 Class II Selv. Dimmable Push-Dimm Or 1.10V

OPTIONAL Accessory

F990H010000

Recessed 3-module junction box (model 503)







OPTIONAL Power supply

RF25754

'Power supply dual function Vout 24Vdc: 8W/100÷240V lout 350ma: 6x1W/100÷240V IP20 Class II selv._Non Dimmable OPTIONAL Power supply

RF25757

Power supply 24V 10W / 110-240V IP67 Class II selv._Non Dimmable OPTIONAL Power supply

RF25752

Power supply 24Vdc 20W / 220-240V IP67 Class II selv. Non Dimmable