

FLOS

 F012B02C037.A Burgundy Red/Black Lava

IC F2 Outdoor H 1852 mm NEW


Designed by Michael Anastassiades, 2019



Bulb not included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100% (with dimmable LED bulb).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

EAN	8054793219530
Mounting	Floor
Environments	Outdoor wet location
Light source type	Bulb
Light sources included	No
Number of lamps	1



Physical

Colour	Burgundy Red/Black Lava
Trim	No
Orientation	Fixed
Net weight (kg)	17.68
IP internal	65

Download

Mounting instructions [ZIP](#)



Photometric Files

LDT / IES



Technical Drawings

2D



3D



BIM




Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmer on board
Dimming interface	Switch Integrated (Remote Dimmable)
Emergency	No

Notes

Bulb not included. LED: max 15W - E27

Bulbs



NOT INCLUDED

RF32288

LED Lamp E27 15W 2700K T38

NOT INCLUDED

RF32289

LED Lamp E27 15W 3000K T38