

## In-Finity 35 Recessed Trim 3000K General Lighting


Designed by FLOS Architectural, 2017



LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                                 |
|------------------------|---------------------------------|
| Mounting               | Wall recessed, Ceiling recessed |
| Environments           | Indoor dry location             |
| Light source type      | LED                             |
| Light sources included | Yes                             |
| LED type               | Top LED                         |
| Lamp category          | LED                             |
| Number of lamps        | 1                               |
| Power (W)              | 13                              |
| Lumen Output (lm)      | 657                             |

### Physical

|                     |       |
|---------------------|-------|
| Colour              | White |
| Trim                | Yes   |
| Orientation         | Fixed |
| Recessed depth (mm) | 120   |
| Length (mm)         | 565   |
| Net weight (kg)     | 1.28  |
| IP internal         | 20    |
| IP external         | 40    |

### Download

|                       |                              |
|-----------------------|------------------------------|
| Mounting instructions | <a href="#">Download PDF</a> |
| Mounting instructions | <a href="#">Download PDF</a> |

### Photometric Files


|           |                              |
|-----------|------------------------------|
| LDT / IES | <a href="#">Download ZIP</a> |
|-----------|------------------------------|

### Technical Drawings

|    |                              |
|----|------------------------------|
| 2D | <a href="#">Download ZIP</a> |
| 3D | <a href="#">Download ZIP</a> |



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 3000      |
| CRI>                   | 80        |
| Beam angle C0-180 (°)  | 110       |
| Beam angle C90-270 (°) | 110       |

Electrical

|                    |              |
|--------------------|--------------|
| Insulation class   | I            |
| Frequency (Hz)     | 50/60        |
| Main voltage (Vac) | 220-240      |
| Power supply       | Integrated   |
| Dimmable           | No           |
| Power supply type  | Non Dimmable |
| Emergency          | No           |

Notes

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. /  
Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

Accessories & Power Supply

|                                                                                   |                                                                                   |                                                                                    |                                                                                     |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
| REQUIRED<br>Accessory                                                             | REQUIRED<br>Accessory                                                             | REQUIRED<br>Accessory                                                              | OPTIONAL<br>Accessory                                                               |
| 08.9051.02                                                                        | 08.9051.40                                                                        | 08.9051.NS                                                                         | 08.0109.00                                                                          |
| Metal cover. Recessed Trim. 35 mm (Colour Anodized Grey)                          | Metal cover. Recessed Trim. 35 mm (Colour White)                                  | Metal cover. Recessed Trim. 35 mm (Colour Black)                                   | 500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room  |