



N35T054U02BDA Anodized Grey

In-Finity 35 Recessed Trim 4000K Micro-Prismatic Diffuser Dali


Designed by FLOS Architectural, 2017



LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Wall recessed, Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	13
Lumen Output (lm)	 553

Physical

Yes
Fixed
120
565
1.28
20
40

Down	load
	luau

lounting instructions	⊥ PD
lounting instructions	⊥ PD

Photometric Files

LDT / IES



Technical Drawings

2D		L ZIP
3D	2	ZIP









https://professional.flos.com/en/global/product/in-finity-35-recessed-trim-4000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic-diffuser-dali-n35t054u02bda/2000k-micro-prismatic

N35T054U02BDA

Schematic light drawing



Beam Angle:		75°
h(m)	E(lx)	D(m)
1	359	1.25
2	90	2.50
3	40	3.76
4	22	5.01

14

6.26

5

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	76
Beam angle C90-270 (°)	64

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable DALI 1
Emergency	No

Notes

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

Accessories & Power Supply



REQUIRED Accessory

08 9051 01

Metal cover. Recessed Trim. 35 mm (Colour Anodized Grey)



REQUIRED Accessory

08.9051.40

Metal cover. Recessed Trim. 35 mm (Colour White)



REQUIRED Accessory

08.9051.NS

Metal cover. Recessed Trim. 35 mm (Colour Black)



OPTIONAL Accessory

08.0112.00

500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam