


FLOS

■ N70T054G14BDA Black

In-Finity 70 Recessed Trim 4000K General Lighting Dali


Designed by FLOS Architectural, 2017



LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Wall recessed, Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Power (W)	13
Lumen Output (lm)	1367

Physical

Colour	Black
Trim	No
Orientation	Fixed
Recessed depth (mm)	135
Length (mm)	565
Net weight (kg)	3.60
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	102
Beam angle C90-270 (°)	106

Electrical

Insulation class	I
Frequency (Hz)	50/60
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable DALI 1
Emergency	No

Notes

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. /
Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

Accessories & Power Supply

			
REQUIRED Accessory	REQUIRED Accessory	REQUIRED Accessory	OPTIONAL Accessory
08.9053.02	08.9053.40	08.9053.NS	08.0110.00
Metal cover. Recessed Trim. 70 mm (Colour Anodized Grey)	Metal cover. Recessed Trim. 70 mm (Colour White)	Metal cover. Recessed Trim. 70 mm (Colour Black)	500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room