

FLOS

■ F018F22BU30 Black

In Vitro Rod 2

Designed by Philippe Starck, 2020

799lm - 2700K - CRI> 80 - Beam° 111



Rod installation. Light source is included. Power supply ON/OFF or dimmable 100-127V is integrated within the ceiling base. Length: 290 mm.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

EAN	8054793319100
Mounting	Suspension
Environments	Outdoor wet location
Light Source Type	LED
Light sources included	Yes
LED type	Edge Lighting
Number of lamps	1
System power (W)	13
System flux (lm)	799

Physical

Color	Black
Orientation	Fixed
Net weight (lb)	10.06
Package height (in)	11.02
Package width (in)	38.03
Package length (in)	11.02
Package volume (in)	4621.59
IP internal	66



Download

Family spec sheet [ZIP](#)
Mounting instructions [ZIP](#)

Photometric Files


LDT / IES [ZIP](#)



Ecodesign and Energy Labelling




Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Schematic light drawing



Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	111
Beam angle C90-270 (°)	111
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	100-127
Driver	Integrated
Dimmable	Yes
Dimming interface	Dimmer Integrated