

# FLOS

F018F32BU01 White

## In Vitro Rod 2

Designed by Philippe Starck, 2020

855lm - 3000K - CRI> 80 - Beam° 111



Rod installation. Light source is included. Power supply ON/OFF or dimmable 100-127V is integrated within the ceiling base. Length: 290 mm.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                      |
|------------------------|----------------------|
| EAN                    | 8054793319827        |
| Mounting               | Suspension           |
| Environments           | Outdoor wet location |
| Light Source Type      | LED                  |
| Light sources included | Yes                  |
| LED type               | Edge Lighting        |
| Number of lamps        | 1                    |
| System power (W)       | 13                   |
| System flux (lm)       | 855                  |

### Physical

|                     |         |
|---------------------|---------|
| Color               | White   |
| Orientation         | Fixed   |
| Net weight (lb)     | 10.06   |
| Package height (in) | 11.02   |
| Package width (in)  | 38.03   |
| Package length (in) | 11.02   |
| Package volume (in) | 4621.59 |
| IP internal         | 66      |



### Download

Family spec sheet [ZIP](#)

Mounting instructions [ZIP](#)

### Photometric Files

LDT / IES [ZIP](#)




### Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional

Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Light distribution     | Symmetric |
| CCT (K)                | 3000      |
| CRI>                   | 80        |
| Beam angle C0-180 (°)  | 111       |
| Beam angle C90-270 (°) | 111       |
| Extreme cut off        | No        |

Electrical

|                    |                   |
|--------------------|-------------------|
| Insulation class   | I                 |
| Frequency (Hz)     | 50/60             |
| Main voltage (Vac) | 100-127           |
| Driver             | Integrated        |
| Dimmable           | Yes               |
| Dimming interface  | Dimmer Integrated |