FLOS

F017D1AB006 Grey

Ingraze Fixed Frame L 1200

Designed by FLOS Outdoor, 2023

2736lm - 2200K - CRI> 80 - Beam° 16

High-power LED source included and rear lenses. 1-10V or DALI on-off and dimmable 220-240V power supply. Compulsory installation box to be ordered separately. Pre-wired with H2O Stop quick connectors, lug/socket included. ACT (Anti-Corrosion Treatment) upon request.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

EAN	8054793272368
Mounting	In-ground
Environments	Outdoor wet location
LED type	Power LED
System power (W)	33.5
Lumen Output (lm)	2736

Physical

Colour	Grey
Orientation	Fixed
Length (mm)	1200
Net weight (kg)	6.76
Package height (mm)	235
Package width (mm)	180
Package length (mm)	1272
Package volume (m3)	0.05
IP internal	66
IP external	67
Static load (kg)	2500.000

Download

Mounting instructions ZIP

Photometric Files

LDT / IES ZIP

Technical Drawings

2D ZIP

3D ZIP

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

https://professional.flos.com/en/global/product/ingraze-fixed-frame-l-1200-f017d1ab006/ F017D1AB006

©2022 Flos - P.IVA 00290820174 - 11/7/2025

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing



Luminous flux luminaire
2736 lm

Beam Angle: 16°

h(m)	E(lx)	D(m)
1	19040	0.27
2	4760	0.55
3	2116	0.82
4	1190	1.09
5	762	1.37

Photometric

Light distribution	Roto symmetric
CCT (K)	2200
CRI>	80
Beam angle C0-180 (°)	16
Beam angle C90-270 (°)	16

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Power supply type	Dimmable 1-10V

©2022 Flos - P.IVA 00290820174 - 11/7/2025

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.



REQUIRED
Frame

Installation

F017Z040000

Framed installation box for single flush installations L 1200

REQUIRED
Frame

Installation

F017Z140000

Framed/frameless installation box for single installations L 1200

REQUIRED
Accessory

Electrical

F990C082000

5-pin connector kit with detachable socket + EU plug.

REQUIRED
Accessory

Electrical

F990C083000

4-pin connector kit with detachable socket + EU plug.

OPTIONAL
Accessory

F990C010000

3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)

OPTIONAL
Frame

Installation

F017Z240000

Framed flush continuous line module L 1200

OPTIONAL
Frame

Installation

F017Z241000

Framed/frameless continuous line module L 1200

OPTIONAL
Frame

Installation

F017Z490000

Standard end-plate cover kit.

©2022 Flos - P.IVA 00290820174 - 11/7/2025

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

OPTIONAL
Frame

Installation

F017Z530000

Standard connecting plate kit.

OPTIONAL
Frame

Installation

F017Z531000

Anti-theft connecting plate kit.

OPTIONAL
Frame

Installation

F017Z550006

Framed anti-theft bracket kit.

OPTIONAL
Frame

Installation

F017Z550033

Framed anti-theft bracket kit.

OPTIONAL
Frame

Installation

F017Z560006

Frameless anti-theft bracket kit.

OPTIONAL
Frame

Installation

F017Z560033

Frameless anti-theft bracket kit.

OPTIONAL
Frame

Installation

F017Z640000

Complete framed anti-theft installation box for single flush installations L 1200

OPTIONAL
Frame

Installation

F017Z740000

Framed/frameless anti-theft installation box for single installations L 1200

©2022 Flos - P.IVA 00290820174 - 11/7/2025

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

OPTIONAL
Accessory

F990C030000

4 way junction box 5 poles IP68 (6-14 mm cables)

OPTIONAL
Accessory

F990C00A000

2 way terminal block 4 poles IP68 H20 stop. (ø5,5÷12mm cable)

OPTIONAL
Accessory

F990C080000

Connector kit 5-pole flying socket + EU plug IP68.

OPTIONAL
Accessory

Electrical

F990C081000

4-pin connector kit with detachable socket + IP68 EU plug.

©2022 Flos - P.IVA 00290820174 - 11/7/2025

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.