

Inner Corner. Can be powered


Designed by FLOS Architectural, 2015



Length: 178 - Ceiling surface, Wall surface

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

| | |
|------------------------|-------------------------------|
| Mounting | Ceiling surface, Wall surface |
| Environments | Indoor dry location |
| Light sources included | no |

Physical

| | |
|-----------------|-------|
| Colour | Black |
| Trim | No |
| Length (mm) | 178 |
| Net weight (kg) | 0.76 |
| IP internal | 20 |
| IP external | 20 |

Download

Mounting instructions



Electrical

Forward voltage (V) 24

Accessories & Power Supply



OPTIONAL
Power supply
Electrical

60.9352
LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.



OPTIONAL
Power supply
Electrical

60.9089
Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W



OPTIONAL
Power supply
Electrical

60.9407
Electronic transformer with constant voltage (24V) for LED. 100/240V. 120W



OPTIONAL
Control interface
Electrical

60.9678A
LED module Dali/Push dimmable control unit for 12, 24 or 48Vdc



OPTIONAL
Installation

08.8887.14A
Endcap. 2 unit kit