


FLOS

F3150054 Natural

IPNOS OUTDOOR Anodized Natural

Designed by Nicoletta Rossi and Guido Bianchi, 2014




15W - 3500K - CRI> 85

Floor lamp providing diffused light. Extruded aluminium frame 10x10x1 gratiné and anodized in various finishes. Leds on the top edges incorporated in the extrusions and burnished into the resin, guaranteeing the IP level. ON/OFF switch in the IP box containing the drivers. Two-pole spark-proof schuko plug.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)




Main specifications

EAN	8059607017456
Mounting	Floor
Environments	Indoor Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	15

Physical

Colour	Natural
Length (mm)	350
Cord colour	Black
Net weight (kg)	1.15
Package height (mm)	745
Package width (mm)	465
Package length (mm)	465
Package volume (m3)	0.16
IP internal	55

Download

[Mounting instructions](#)  PDF

Photometric Files

[LDT / IES](#)  ZIP


Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Schematic light drawing



Beam Angle: 73°

h(m)	E(lx)	D(m)
1	337	1.49
2	84	2.98
3	37	4.47
4	21	5.96
5	13	7.44

Luminous flux Luminaire
744 lm

Photometric


Light distribution	Symmetric
CCT (K)	3500
CRI>	85
Extreme cut off	No

Electrical


Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Power supply	Integrated
Dimmable	No
Power supply type	Electronic 24V
Dimming interface	Switch Integrated (Not Dimmable)
Plug type	Type C
Batteries inside	No
Charging min time	NO

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Accessories & Power Supply



OPTIONAL
Accessory

F3125000

Ipnos Top Plate