

## Johnny 80 Semi-Recessed 1L Square 1-10V - 277V

Designed by FLOS Architectural



Semi-recessed luminaire with LED light source. Power supply not included.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 6.2                 |
| System flux (lm)       | 311                 |

### Physical

|                          |                |
|--------------------------|----------------|
| Color                    | Concrete/Black |
| Trim                     | Yes            |
| Orientation              | Adjustable     |
| Longitudinal tilting (°) | 20             |
| Transversal tilting (°)  | 20             |
| Net weight (lb)          | 0.82           |
| Package volume (in)      | 916            |
| IP internal              | 20             |



### Download

[Family spec sheet](#) [ZIP](#)


[Mounting instructions](#) [PDF](#)

### Photometric Files

[LDT / IES](#) [ZIP](#)



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 3000      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 31        |
| Beam angle C90-270 (°) | 31        |

Electrical

|                    |                |
|--------------------|----------------|
| Insulation class   | I              |
| Frequency (Hz)     | 50/60          |
| Main voltage (Vac) | 277            |
| LED current (mA)   | 500            |
| Driver             | Integrated     |
| Dimmable           | Yes            |
| Dimming type       | Dimmable 1-10V |

Notes

Accessories included (honeycomb and screening crosspiece).



OPTIONAL  
Housing and Hanger Bar

TRAY-0027

Registration Tray - non electrical,  
place holder for non IC new  
construction, Johnny 80 1 Light  
Semi-recessed, 2.99 x 2.99"