

03.0700.40A7U White

## Johnny Ø 80 Trim 1L Round 1-10V - 277V

Designed by FLOS Architectural



Recessed luminaire with LED light source. Power supply not included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 6.2                 |
| Source flux (lm)       | 600                 |
| System flux (lm)       | 399                 |

### Physical

|                          |            |
|--------------------------|------------|
| Color                    | White      |
| Trim                     | Yes        |
| Orientation              | Adjustable |
| Longitudinal tilting (°) | 20         |
| Transversal tilting (°)  | 20         |
| Net weight (lb)          | 0.55       |
| Package volume (in)      | 916        |
| IP internal              | 20         |



### Download

Family spec sheet [↓ ZIP](#)  
Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 3000      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 11        |
| Beam angle C90-270 (°) | 11        |


Electrical

|                    |                 |
|--------------------|-----------------|
| Insulation class   | I               |
| Frequency (Hz)     | 50/60           |
| Main voltage (Vac) | 277             |
| LED current (mA)   | 500             |
| Driver             | Remote included |
| Dimmable           | Yes             |
| Dimming type       | Dimmable 1-10V  |

Notes

Accessories included (honeycomb and screening crosspiece).

Accessories & Power Supply



OPTIONAL  
Housing and Hanger Bar

TRAY-0001

Registration Tray - non electrical,  
place holder for non IC new  
construction, Ø2.95"